




**iAM**


Petrochemical  
Company

---

Global. Distinguished



# HDPE MSDS



## Material Safety Data Sheet (MSDS)


Page: 1 of 8

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Revision Number: 1

Product Name:

**HDPE**  
**High Density Polyethylene**



### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/ UNDERTAKING

**Identification of the substance or preparation:**

**Country of origin:**

**CAS Number:**

**Synonyms:**

**Company/undertaking identification**

**High Density Polyethylene**

**Iran (Islamic Republic of Iran)**

**9002-88-4**

**HDPE, PE-HD**

**Jam Petrochemical Company**

**Manufacturer subcontractor:**

**Emergency phone number:**

**Contact email:**

**Fax:**

**Association/Organization:**

**Use of the Substance / Preparation:**

**(JPC)**

**00982188654545**

**info@jpcomplex.com**

**00982188771426**

**None**

**Plastic bottle, Corrosion Resistant pipe and tubing, cable coating, Blow molded packaging, medical packing, adhesive ...**

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous substances:**

**Hazardous label(s):**

**Toxicological characteristics:**

**Substances present at a concentration below the minimum danger:**

**Other component:**

**Not applicable, Inert substance.**

**This product is not hazardous**

**This product is not toxic.**

**Within the present knowledge of the supplier, this product does not contain any hazardous ingredients in quantities requiring to report in this section, in accordance with EU or national regulations.**

**None**

### 3. IDENTIFICATION OF HAZARDS

**Risk phrases:**

**Skin contact:**

**Eye contact:**

**Stable product. It doesn't offer hazard in its normal handling and storage state. Negligible hazard at ambient temperatures (-18 to +38 degrees C; 0 to 100 degrees F). Exposure to hot material may cause thermal burns. Particulates may scratch eye surfaces / cause mechanical irritation.**

## Material Safety Data Sheet (MSDS)

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Page: 2 of 8

Revision Number: 1

Product Name:

**HDPE**  
**High Density Polyethylene**



Reactivity
Flammability
Health

### Inhalation :

Dust may cause mechanical irritation.  
Negligible hazard at ambient temperature  
(-18 to 38 Deg C; 0 to 100 Deg F) Vapors  
and/or aerosols which may be formed at  
elevated temperatures may be irritating to  
eyes and respiratory tract.

### If swallowed:

Minimal toxicity.

### Other information:

Product not classified as hazardous by  
UNO.

## 4. FIRST AID MEASURES

**As a general rule, in case of doubt or if symptoms persist, always call a doctor**  
**NEVER induce swallowing in an unconscious person.**

### Skin contact :

Wash skin with soap and water.  
For hot product, immediately immerse in  
or flush the affected area with large  
amounts of cold water to dissipate heat.  
Cover with clean cotton sheeting or gauze  
and get prompt medical attention.

No attempt should be made to remove  
material from skin or to remove  
contaminated clothing, as the damaged  
flesh can be easily torn.

### In case of exposure by inhalation:

In case of adverse exposure to vapors  
and/or aerosols formed at elevated  
temperatures, immediately remove  
the affected victim from exposure.

Administer artificial respiration if  
breathing is stopped. Keep at rest.

Call for prompt medical attention.

### In case of splashes or contact with eyes:

This product is an inert solid. If in eye,  
remove as one would any foreign object.  
Rinse with plenty of running water. Obtain  
medical attention if symptoms occur.

### In case of swallowing:

There is no known acute effect after over-  
exposure to this product.

### Note of physician:

If swallowed, rinse mouth with water (only  
if the person is conscious). Obtain medical  
attention if symptoms occur.  
Do not induce vomiting.

## Material Safety Data Sheet (MSDS)

Page: 3 of 8

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Revision Number: 1

Product Name:

**HDPE**  
**High Density Polyethylene**



Reactivity
Flammability
Health

### 5. FIRE FIGHTING MEASURES

**Flammable class:**

**Flammability Risk 1 (Slight)**

**Suitable extinguishing media:**

Use water spray to cool fire exposed surfaces, protect personnel, and extinguish the fire. For small fire, use dry chemical or CO<sub>2</sub>. For large fire, Use dry chemical powder or alcohol-resistant foam.

**Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases:**

In case of fire, may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, (dense) black smoke, aldehydes, and Organic acids.

**Special protective equipment for fire fighting :**

Respiratory and eye protection required for fire fighting personnel.

**Other information:**

Solid material, may burn at or above the flashpoint, and airborne dust may explode if ignited. If thermally decomposed, flammable/toxic gases may be released. Toxic gases will form upon combustion. Static Discharge, material can accumulate static charges which can cause an incendiary electrical discharge

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:**

Avoid creating dusty conditions and prevent wind dispersal. Use suitable protective equipment .Keep away from sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. No special measures required.

**Environmental precautions:**

**Methods for cleaning up and disposal:**

Small spill and leak - Vacuum or sweep up material and place in a designated labelled waste container. Clean up affected area with a large amount of water.

Large spill and leak - Use explosion-proof electrical (ventilating, lighting and material handling) equipment.

**Other information:**

Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Recover the spilled material and place in suitable containers

## Material Safety Data Sheet (MSDS)

Page: 4 of 8

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Revision Number: 1

Product Name:

**HDPE**  
**High Density Polyethylene**



Reactivity
Flammability
Health

for recycle or disposal.

### 7. HANDLING AND STORAGE

The regulations relating to storage premises apply to workshop where the product is handled

#### Handling:

Use with adequate ventilation. Local exhaust ventilation should be provided. Avoid creating dusty conditions and prevent wind dispersal. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Take measures against static discharge. Keep away from sources of ignition.

#### Storage:

Store in a fireproof location. Keep away from incompatible materials and avoid specific conditions. Containers should be grounded. Take precautionary measures against electrostatic discharges. Do not stack more than 2 pallets high in connection with risk of falling over. Do not stack pallets with grades containing slip or Anti-Block (AB) additives. Protect from (sun) light. Keep in a dry place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Exposure limit values:

5 mg/m<sup>3</sup> (respirable dust), and 10 mg/m<sup>3</sup> (total inhalable dust) based on the OSHA PEL for nuisance dust. The recommended permissible exposure levels indicated above reflect the levels revised by OSHA in 1989 or in subsequent regulatory activity. NPC recommends that the lower exposure levels be observed as reasonable worker protection.

#### Exposure controls:

Local exhaust ventilation of process equipment may be needed to control particulate exposures to below the recommended exposure limit.

#### Personal protective equipment:

For open systems at ambient temperature (-18 to 38 degrees C) where contact is likely, wear safety glasses with side shields. Where contact may occur with hot material, wear thermal resistant gloves, arm protection, and

## Material Safety Data Sheet (MSDS)


Page: 5 of 8

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Revision Number: 1

Product Name:

### HDPE High Density Polyethylene



Reactivity
Flammability
Health

Eye protection:  
Respiratory protection:  
Hand protection:

Skin and body protection:  
Health measures:  
Environmental exposure controls:

a face shield.  
Safety glasses with side shields.  
Wear dust protection mask P2.  
When handling hot material, wear heat-resistant protective gloves that are able to withstand the temperature of molten product.  
Working clothes.  
Not available  
Plastic pellets are defined as a "significant material" which requires any industrial plant that may expose pellets to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other Clean Water Act violations.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

General information:  
Appearance (at 20°C):  
Colour:  
Odour:  
PH (at 20°C):  
Freezing /Melting point (°C):  
Boiling point/range (°C):  
Flash point (°C):  
Flammability:  
Auto-ignition temperature:  
Explosive properties:  
Oxidising properties:  
Vapour pressure (at 20°C):  
Density (at 20°C):  
Solubility (at 20°C):

Viscosity (40°C):  
Evaporation rate:  
Other information:

None  
Solid. (Granular solid. Powder.)  
Off-white.  
Wax-like when heated  
Not applicable.  
125-145  
Decomposes. >300 °C  
>343 °C  
Flammability Risk 1 (Slight)  
> 330 °C  
None  
None  
Not available  
0.941 to 0.97 g/cm<sup>3</sup>  
water solubility: Insoluble in cold water  
solubility in fats: Insoluble  
Not applicable  
Not applicable  
Insoluble in almost all solvents at room temperature; soluble in many organic solvents above 93 deg C; may "swell" by absorption of solvents below 60 deg C

## 10. STABILITY AND REACTIVITY

Stability:

Conditions to avoid:

Stable under recommended storage and handling conditions  
Temperatures over 650 F (343 C) will lead to resin degradation and decomposition. Keep



## Material Safety Data Sheet (MSDS)

Page: 6 of 8

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Revision Number: 1

Product Name:

### HDPE High Density Polyethylene



Reactivity
Flammability
Health

Material to avoid:

Hazardous decomposition products:

away from heat, sparks and flame and exposure to (sun) light. Prevent formation of dust clouds. Take measures against static discharge. Avoid storage or contact with strong oxidizing agents.

Fluorine Strong Oxidizing agents.  
Highly dependent on temperature and environmental conditions, a variety of decomposition products may be formed, such as low molecular weight hydrocarbons and hydrocarbon oxidation products (acids, ketons, and aldehydes). Also thermal decomposition under condition of limited oxygen supply will give rise to carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity:

- LD<sub>50</sub>, oral, rat (mg.kg<sup>-1</sup>): >5000 mg/kg
- LD<sub>50</sub>, oral, mouse (mg.kg<sup>-1</sup>): Not Available
- LD<sub>50</sub>, dermal (mg.kg<sup>-1</sup>): Not Available

Sub chronic – chronic toxicity:

None

Sensibilization:

Not available

Carcinogenicity:

Carcinogenic effects are not known.

Reproductive effects:

Reproductive effects are not known.

Human experience:

Not available

Other information:

During heating and processing of the material small amounts of free monomer may evaporate resulting in airborne concentration that may cause irritating effects of the respiratory tract and nausea.

## 12. ECOLOGICAL INFORMATION

Ecotoxicity:

No specific ecological data are available for this product.

Bioaccumulative potential:

Effects on nature due to bioaccumulation are not known.

Mobility:

No specific ecological data are available for this product.

Persistence and degradability:

No specific ecological data are available for this product.

Other adverse effects:

No specific ecological data are available for this product.

## Material Safety Data Sheet (MSDS)

Page: 7 of 8

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Revision Number: 1

Product Name:

**HDPE**  
**High Density Polyethylene**



Reactivity
Flammability
Health

### 13. DISPOSAL CONSIDERATIONS

**Disposal of product:**

Waste must be disposed of in accordance with national and local environmental regulations. Polyethylene bags should be reused in the working area, products transportation or recycled by specialized companies.

**Disposal of packaging:**

### 14. TRANSPORT INFORMATION

**Land transport:**

Not established

**ADR/RID:**

Not established

**Packaging group:**

Not applicable

**Maritime transport:**

Not applicable

**Air transport:**

Not applicable

### 15. REGULATORY INFORMATION

**Hazardous label(s):**

NPCA-HMIS - NFPA - KEY			
HEALTH	1	1	4=Severe
FLAMMABILITY	1	1	3=Serious
REACTIVITY	0	0	2=Moderate
			1=Slight
			0=Minimal

**Safety phrases:**

This product is not hazardous

**Risk phrases:**

This product is not hazardous

### 16. OTHER INFORMATION

None

## Material Safety Data Sheet (MSDS)

According to the Directives 91/155/CEE-2001/58/CE-ISO 11014-1

Page: 8 of 8

Revision Number: 1

Product Name:

**HDPE**  
**High Density Polyethylene**



Reactivity
Flammability
Health

The contents and format of this MSDS are in accordance with EEC Commission Directive 2001/58/EC

### Disclaimer of liability:

*The information in this MSDS was obtained from different sources, which National Petrochemical Company (NPC) and Iran Petrochemical Commercial Company (IPCC) believe, are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, National Petrochemical Company (NPC) and Iran Petrochemical Commercial Company (IPCC) do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.*